



Flange Avulsa PN-16



DN	D	C	d	Parafusos	Parafusos	A	Ressalto	Ressalto	PSA	PMS	PTA
DN	D	C	d	Quant.	Dimensão Nominal	A	g	C	PSA	PMS	PTA
	mm	mm	mm			mm		mm			
50	165	125	19	4	M16	19	99	3	1,60	2,00	2,50
80	200	160	19	8	M16	19	132	3	1,60	2,00	2,50
100	220	180	19	8	M16	19	156	3	1,60	2,00	2,50
150	285	240	23	8	M20	19	211	3	1,60	2,00	2,50
200	340	295	23	12	M20	20	266	3	1,60	2,00	2,50
250	400	355	28	12	M24	22	319	3	1,60	2,00	2,50
300	455	410	28	12	M24	24,5	370	4	1,60	2,00	2,50
350	520	470	28	16	M24	26,5	429	4	1,60	2,00	2,50
400	580	525	31	16	M27	28	480	4	1,60	2,00	2,50
450	640	585	31	20	M27	30	548	4	1,60	2,00	2,50
500	715	650	34	20	M30	31,5	609	4	1,60	2,00	2,50
600	840	770	37	20	M33	36	720	5	1,60	2,00	2,50
700	910	840	37	24	M33	39,5	794	5	1,60	2,00	2,50
800	1025	950	40	24	M36	43	901	5	1,60	2,00	2,50
900	1125	1050	40	28	M36	46,5	1001	5	1,60	2,00	2,50
1000	1255	1170	43	28	M39	50	1112	5	1,60	2,00	2,50
1200	1485	1390	49	32	M45	57	1328	5	1,60	2,00	2,50

Flange: normas NBR 7675 e ISO 2531.