



Flange Avulsa PN-25



DN	D	C	d	Parafusos	Parafusos	A	Ressalto	Ressalto	PSA	PMS	PTA
DN	D	C	d	Quant.	Dimensão Nominal	A	g	C	PSA	PMS	PTA
	mm	mm	mm			mm		mm			
50	165	125	19	4	M16	19	99	3	-	-	-
80	200	160	19	8	M16	19	132	3	4,00	4,80	5,30
100	235	190	23	8	M20	19	156	3	2,50	3,00	3,50
150	300	250	28	8	M24	20	211	3	2,50	3,00	3,50
200	360	310	28	12	M24	22	274	3	2,50	3,00	3,50
250	425	370	31	12	M27	24,5	330	3	2,50	3,00	3,50
300	485	430	31	16	M27	27,5	389	4	2,50	3,00	3,50
350	555	490	34	16	M30	30	448	4	2,50	3,00	3,50
400	620	550	37	16	M33	32	503	4	2,50	3,00	3,50
450	670	600	37	20	M33	34,5	548	4	2,50	3,00	3,50
500	730	660	37	20	M33	36,5	609	4	2,50	3,00	3,50
600	845	770	40	20	M36	42	720	5	2,50	3,00	3,50
700	960	875	43	24	M39	46,5	820	5	2,50	3,00	3,50
800	1085	990	49	24	M45	51	928	5	2,50	3,00	3,50
900	1185	1090	49	28	M45	55,5	1028	5	2,50	3,00	3,50
1000	1320	1210	56	28	M52	60	1140	5	2,50	3,00	3,50
1200	1530	1420	56	32	M52	69	1350	5	2,50	3,00	3,50

Flange: normas NBR 7675 e ISO 2531.